



The Right Connection®

Cam & Groove Vent-Lock™

Dixon offers a range of specialist Cam & Groove Couplings suited to various applications but specifically designed for the oil & gas industry.



Applications:

- Transfer of fluids and solids, with a safer disconnection.

Features:

- safety release cam and groove couplings permit the release of static pressure when disconnecting hose assemblies
- venting system protects operator from being sprayed with hazardous or non-hazardous fluids or solids
- safety orange powder coated cam arms

Material:

- 316 stainless steel as standard
- Other materials available on request

Sizes:

- 1 inch to 3 inch

Attachment Options:

- Ferrules
- Sleeves
- Bands

Pressure & Temperature Ratings:

- rated to 250 PSI, recommendation based on the use of mating Dixon™ L-style fittings at ambient temperature (70°F) with standard Buna-N seal installed
 - 1", 1½" and 2" sizes have a maximum working pressure of 250 PSI
 - 3" maximum working pressure 150 PSI with King Crimp™ ferrules, crimp sleeves and bands at 125 PSI

Consult Dixon for use at elevated temperatures

⚠ WARNING

Does not interchange with standard cam and groove products, use only with Dixon L-style fittings!



Dixon Group Europe Ltd

+44 (0)1772 323529

sale@dixoneurope.co.uk

www.dixoneurope.co.uk

