

PREMVIN - Food & Bulk PVC Suction & Delivery Hose



Technical Characteristics	
Application	Food grade PVC hose for abrasive and non-abrasive solids or liquids including diluted chemicals
Construction	Clear food quality PVC according to EU10/2011
Branding	DIXON PREMVIN SUCTION
Reinforcement	Spring steel
Temperature	-10°C TO +55°C
Safety Factor	3:1

Sizes						
I.D (mm)	O.D (mm)	Max Working Pressure (Bar)	Min Burst Pressure (Bar)	Vacuum	Min Bend Radius (mm)	Weight (Kg/Mtr)
13	19	12	36	0.88	26	0.21
16	22	10.5	33	0.88	32	0.25
19	26	11	33	0.88	38	0.33
25	33	10	33	0.88	50	0.52
32	40	9	30	0.88	80	0.66
38	47	9	30	0.88	95	0.80
51	62	7	27	0.88	128	1.30
63	74	6	24	0.88	158	1.80
76	90	4	15	0.88	190	2.30
102	118	3	9	0.88	255	3.70
127	143	3	9	0.88	381	4.70
152	170	2.5	7	0.88	456	6.90

BESPOKE & SPECIALIST HYGIENIC HOSES AVAILABLE ON REQUEST TO SUIT SPECIFIC APPLICATIONS

All Hose Assemblies compliant with Pressure Equipment Directive 2014/68/EU

We reserve the right to change hose specifications without prior notice